

ORS Series

Features

- 105°C, 15,000 hours assured
- Ultra low ESR with large permissible ripple current
- RoHS Compliance




Marking color: Blue

Specifications

Items	Performance				
Category Temperature Range	-55°C ~ +105°C				
Capacitance Tolerance	±20% (at 120Hz, 20°C)				
Leakage Current (at 20°C)*	Rated voltage applied, after 2 minutes at 20°C. See Standard Ratings				
Tanδ (at 120Hz, 20°C)	See Standard Ratings				
ESR (at 100k – 300k Hz, 20°C)	See Standard Ratings				
Endurance	Test Time	15,000 Hrs			
	Capacitance Change	Within ±20% of initial value			
	Tanδ	Less than 150% of specified value			
	ESR	Less than 150% of specified value			
	Leakage Current	Within specified value			
* The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied for specified hours at 105°C.					
Moisture Resistance	Test Time	1,000 Hrs			
	Capacitance Change	Within ±20% of initial value			
	Tanδ	Less than 150% of specified value			
	ESR	Less than 150% of specified value			
	Leakage Current	Within specified value			
* The above specifications shall be satisfied when the capacitors are restored to 20°C after subjecting them at 60°C, 90 to 95% RH for 1,000 hours. Leakage current should be tested after voltage treatment*.					
Resistance to Soldering Heat* (Please refer to page 11 for soldering conditions)	Capacitance Change	Within ±10% of initial value			
	Tanδ	Less than 130% of specified value			
	ESR	Less than 130% of specified value			
	Leakage Current	Within specified value			
Ripple Current and Frequency Multipliers	Frequency (Hz)	120 ≤ f < 1k	1k ≤ f < 10k	10k ≤ f < 100k	100k ≤ f < 500k
	Multiplier	0.05	0.3	0.7	1.0

* For any doubt about measured values, measure the leakage current again after the following voltage treatment.
Voltage treatment: DC rated voltage is applied to the capacitors for 2 hours at 105°C.

Diagram of Dimensions



Lead Spacing and Diameter

Unit: mm

φD	8	10
L	11.5	12
P	3.5	5.0
φd	0.6	
α	1.0	
β	0.5	

Marking



All product specifications in the catalog are subject to change without notice. (CAT. 2017E1)

Dimension: ϕ D×L(mm)
Ripple Current: mA/rms at 100k Hz

Standard Ratings

W. V. (V)	Surge Voltage (V)	Capacitance (μF)	Size ϕ D×L(mm)	Tanδ (120Hz, 20°C)	L C (μA)	E S R (mΩ/at 100k ~ 300k Hz, 20°C Max)	Rated R. C. (mA/rms at 100k Hz, 105°C)
2.5V(0E)	2.9	680	8 × 11.5	0.12	340	10	5,230
		820	8 × 11.5	0.12	410	10	5,230
		1,500	10 × 12	0.12	750	8	5,500
4V (0G)	4.6	560	8 × 11.5	0.12	448	10	5,230
		820	10 × 12	0.12	656	8	5,500
		1,000	10 × 12	0.12	800	8	5,500
		1,200	10 × 12	0.12	960	8	5,500
6.3V (0J)	7.2	390	8 × 11.5	0.12	491	12	4,770
		470	8 × 11.5	0.12	592	12	4,770
		680	10 × 12	0.12	857	10	5,500
		820	10 × 12	0.12	1,033	10	5,500
		1,000	10 × 12	0.12	1,260	10	5,500
10V (1A)	12.0	270	8 × 11.5	0.12	540	14	4,420
		330	8 × 11.5	0.12	660	14	4,420
		470	10 × 12	0.12	940	12	5,300
		560	10 × 12	0.12	1,360	12	5,300
16V (1C)	18.0	100	8 × 11.5	0.12	320	16	4,360
		180	8 × 11.5	0.12	576	16	4,360
		270	10 × 12	0.12	864	14	5,050
		330	10 × 12	0.12	1,056	14	5,050
20V (1D)	23.0	100	8 × 11.5	0.12	400	24	3,320
		150	10 × 12	0.12	600	20	4,320
25V (1E)	29.0	68	8 × 11.5	0.12	340	24	3,320
		100	10 × 12	0.12	500	20	4,320
35V (1V)	40.0	18	8 × 11.5	0.12	315	34	2,830
		33	10 × 12	0.12	578	30	3,270

OP-CAP

Part Numbering System

ORS Series	470μF	±20%	6.3V	Bulk Package	Gas Type	8 ϕ × 11.5L	Pb-free and PET coating case
ORS	471	M	OJ	BK	-	0811	S
Series Name	Capacitance	Capacitance Tolerance	Rated Voltage	Lead Configuration & Package	Rubber Type	Case size	Lead Wire and Coating Type
							Supplement Code

Note: For more details, please refer to "Part Numbering System (Radial Type)".

All product specifications in the catalog are subject to change without notice. (CAT. 2017E1)