

Type	Description	Life Time (hours)	SURGE - LELON series	Type	Description	Life Time (hours)	SURGE - LELON series
OP-CAP	105°C, Standard, Chip	2K	OCV	Pen Type	105°C	2K	RGL
	105°C, Low ESR, Chip	2K	OCVZ		105°C, Long Life	5K	RPL
	125°C, Wide temp., Chip	2K	OCVU		105°C, Long Life, Downsized	10K	RQL
	105°C, Long Life	5K	OVK		105°C, High Ripple	2K	RXR
	105°C, Ultra Low ESR	2K	OVH	Low Leakage	85°C Standard	1K ~ 2K	RLA
	105°C, Standard, Radial	2K	OCR		105°C Standard	1K	RA
	105°C, Low ESR, Radial	2K	OCRZ		85°C, 7mmL	2K	SLA
	105°C, Low ESR, Radial	5K	OCRK		105°C, 7mmL	1K	SA
	125°C, Wide temp., Radial	2K	OCRU		85°C, 5mmL	1K	SSL
	105°C, Ultra Low ESR, Long Life	5K	ORE	Mini size	85°C, Standard	1K ~ 2K	SEA
85°C, Standard	2K	VE	105°C, Standard		1K	SG	
85°C, 4.5mmL	2K	VSS	105°C, Wide Temp. Range		1K ~ 2K	SJA	
105°C, 5.5mmL	1K ~ 2K	VES	85°C, Standard, 5mmL		1K	SS	
105°C, Standard	2K	VEJ (VGA)	105°C, Standard, 5mmL		1K	SSG	
105°C, Long Life	3K	VEU	105°C, Low Imp., 5~7mmL		1K	SXJ	
105°C, Low ESR, Smaller Size	1K	VEZ	Non. & Bi. Polarized		85°C, Standard	2K	RN
105°C, Low Imp. & ESR	2K	VEH		105°C, Standard	2K	RNG	
105°C, Low ESR, Long Life	2K-5K	VZH		85°C, 7mmL	1K	SN	
105°C, Low ESR, Long Life	2K	VZL		85°C, 5mmL	1K	SSN	
105°C, Anti-vibration	5K	VLV	Snap-in	85°C, Standard	2K	LS	
105°C, Ultra Low ESR, High CV	2K ~ 5K	VZS		85°C, Over Voltage Operation	2K	LS2	
125°C, Standard	1K	VUA		105°C, Standard	2K	LSG	
125°C, Extra Long Life	5K	VUK		105°C, Long Life	3K	LSM	
125°C, Anti-vibration	2K	VLW		105°C, High Ripple	3K	LSR	
85°C, Bi-polarized	2K	VEB		105°C, Long Life	5K	LSK	
85°C, Low Leakage Current	2K	VEC		105°C, Charge/Discharge	3K	LHM	
Standard	85°C, Standard	2K ~ 3K		REA	Screw	85°C, Standard	2K
	105°C, Standard	2K	RGA	85°C, Standard		5K	MEK
	105°C, Wide Temp. Range	2K	RJA	85°C, Long Life		20K	MEQ
	130°C, Standard	2K	RUA	105°C, Standard		2K	MGA
	125°C, Low Voltage	3K ~ 5K	RUK	105°C, Long Life		5K	MGK
85°C, Standard	2K	REX	85°C, Charge/Discharge	5K		MKR	
High Reliability	105°C, Low ESR	2K	RXY	Flame Retardant	85°C, Standard	2K	LV
	105°C, Low ESR	2K ~ 5K	RXJ		105°C, Standard	2K	LVG
	105°C, Downsize	2K ~ 5K	RXK		85°C, Standard, Radial	2K	REV
	105°C, Low ESR	3K ~ 6K	RXW		105°C, Standard, Radial	2K	RGV
Ballast	105°C, Low ESR	4K ~ 10K	RZW	<p>For more info please call us at (631) 595-1818 www.surgecomponents.com</p>			
	105°C, Standard	3K	RXC				
	105°C, Downsize	5K	RXB				
	105°C, Long Life, Downsized	10K	RXQ				