



N-Channel Enhancement Mode MOSFET

Features

- Extremely low threshold voltage
- Halogen and Antimony Free(HAF), RoHS compliant

Applications

- Portable appliances
- High speed switch
- Battery management
- Low power DC to DC converter



TO-247 Plastic Package
1.Gate 2.Drain 3.Source

Key Parameters

Parameter	Value	Unit
BV_{DSS}	150	V
$R_{DS(ON)}$ Max	8.5 @ $V_{GS} = 10$ V	m Ω
	10.5 @ $V_{GS} = 6$ V	
$V_{GS(th)}$ typ	2.9	V
Q_g typ	145 @ $V_{GS} = 10$ V	nC

Absolute Maximum Ratings(at $T_a = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	150	V
Gate-Source Voltage	V_{GS}	± 25	V
Drain Current	I_D	86	A
		54	
Peak Drain Current, Pulsed ¹⁾	I_{DM}	400	A
Avalanche Current	I_{AS}	51.8	A
Single Pulse Avalanche Energy ²⁾	E_{AS}	670.8	mJ
Power Dissipation	P_{tot}	79.1	W
Operating Junction and Storage Temperature Range	T_J, T_{stg}	- 55 to + 150	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Max.	Unit
Thermal Resistance from Junction to Case	$R_{\theta JC}$	1.58	$^\circ\text{C/W}$
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	33	$^\circ\text{C/W}$

¹⁾ Pulse Test: Pulse Width ≤ 100 μs , Duty Cycle $\leq 2\%$, Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)} = 150^\circ\text{C}$.

²⁾ Limited by $T_{J(MAX)}$, starting $T_J = 25^\circ\text{C}$, $L = 0.5$ mH, $R_g = 25$ Ω , $I_{AS} = 51.8$ A, $V_{GS} = 10$ V.

Characteristics at $T_a = 25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Min.	Typ.	Max.	Unit
STATIC PARAMETERS					
Drain-Source Breakdown Voltage at $I_D = 1\text{ mA}$	BV_{DS}	150	-	-	V
Drain-Source Leakage Current at $V_{DS} = 150\text{ V}$	I_{DSS}	-	-	1	μA
Gate Leakage Current at $V_{GS} = \pm 25\text{ V}$	I_{GSS}	-	-	± 100	nA
Gate-Source Threshold Voltage at $V_{DS} = V_{GS}$, $I_D = 250\text{ }\mu\text{A}$	$V_{GS(th)}$	2	-	4	V
Drain-Source On-State Resistance at $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$ at $V_{GS} = 6\text{ V}$, $I_D = 25\text{ A}$	$R_{DS(on)}$	- -	6.5 -	8.5 10.5	m Ω
DYNAMIC PARAMETERS					
Forward Transconductance at $V_{DS} = 5\text{ V}$, $I_D = 30\text{ A}$	g_{fs}	-	74	-	S
Gate Resistance at $V_{GS} = 0\text{ V}$, $V_{DS} = 0\text{ V}$, $f = 1\text{ MHz}$	R_g	-	1.7	-	Ω
Input Capacitance at $V_{GS} = 0\text{ V}$, $V_{DS} = 75\text{ V}$, $f = 1\text{ MHz}$	C_{iss}	-	9434	-	pF
Output Capacitance at $V_{GS} = 0\text{ V}$, $V_{DS} = 75\text{ V}$, $f = 1\text{ MHz}$	C_{oss}	-	608	-	pF
Reverse Transfer Capacitance at $V_{GS} = 0\text{ V}$, $V_{DS} = 75\text{ V}$, $f = 1\text{ MHz}$	C_{rss}	-	34	-	pF
Gate charge total at $V_{DS} = 75\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$ at $V_{DS} = 75\text{ V}$, $V_{GS} = 6\text{ V}$, $I_D = 30\text{ A}$	Q_g	- -	145 93	- -	nC
Gate to Source Charge at $V_{DS} = 75\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$	Q_{gs}	-	41	-	nC
Gate to Drain Charge at $V_{DS} = 75\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$	Q_{gd}	-	35	-	nC
Turn-On Delay Time at $V_{DS} = 75\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$, $R_g = 3.3\text{ }\Omega$	$t_{d(on)}$	-	52	-	ns
Turn-On Rise Time at $V_{DS} = 75\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$, $R_g = 3.3\text{ }\Omega$	t_r	-	63	-	ns
Turn-Off Delay Time at $V_{DS} = 75\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$, $R_g = 3.3\text{ }\Omega$	$t_{d(off)}$	-	48	-	ns
Turn-Off Fall Time at $V_{DS} = 75\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 30\text{ A}$, $R_g = 3.3\text{ }\Omega$	t_f	-	13	-	ns
Body-Diode PARAMETERS					
Drain-Source Diode Forward Voltage at $I_S = 1\text{ A}$, $V_{GS} = 0\text{ V}$	V_{SD}	-	-	1.3	V
Body-Diode Continuous Current	I_S	-	-	86	A
Body-Diode Continuous Current, Pulsed	I_{SM}	-	-	400	A
Body Diode Reverse Recovery Time at $I_S = 30\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$	t_{rr}	-	118	-	ns
Body Diode Reverse Recovery Charge at $I_S = 30\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$	Q_{rr}	-	541	-	nC

Electrical Characteristics Curves

Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 On-Resistance vs. Drain Current




Fig. 4 On-Resistance vs. Gate to Source Voltage




Fig. 5 On-Resistance vs. T_J





Fig. 6 Typical Body-Diode Forward Characteristics



Electrical Characteristics Curves

Fig. 7 Typical Junction Capacitance




Fig. 8 Drain-Source Leakage Current vs. Tj




Fig. 9 V(BR)DSS vs. Junction Temperature




Fig. 10 Gate Threshold Variation vs. Tj




Fig. 11 Gate Charge













Fig. 12 Safe Operation Area




Electrical Characteristics Curves
Fig. 13 Normalized Maximum Transient Thermal Impedance($z_{\theta JC}$)

Fig. 14 Normalized Maximum Transient Thermal Impedance($z_{\theta JA}$)


Test Circuits
Fig.1-1 Switching times test circuit

Fig.1-2 Switching Waveform

Fig.2-1 Gate charge test circuit

Fig.2-2 Gate charge waveform

Fig.3-1 Avalanche test circuit

Fig.3-2 Avalanche waveform


Package Outline Dimensions (Units: mm)

TO-247



UNIT	A	B	C	D	E	F	G	W	H	H1	K	L	M	P
mm	6.5	5.2	0.7	20.3	2.2	1.3	5.7	16.2	5.3	2.5	4.45	21.3	3.2	16.6
	5.9	4.6	0.5	19.7	1.8	1.1	5.1	15.8	4.7	2.1	4.05	20.7	2.8	16.2

UNIT	P1	Q	Q1
mm	14.2	7.35	4.2
	13.8	7.05	3.6

Packing information

Package	Carton Quantity	Box Quantity	Base Quantity	Delivery Mode
TO-247	2.88 K / Carton	720 pcs / Box	30 pcs / Tube	Tube

Marking information

" TPT15N065S " = Part No

" ***** " = Date Code Marking

Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.