



N-Channel Enhancement Mode MOSFET

Features

- Advanced trench Cell Design
- Low Thermal Resistance
- Halogen and Antimony Free(HAF), RoHS compliant

Applications

- DC - DC Converter
- Motor drivers



1.Gate 2.Drain 3.Source
TO-220FB Plastic Package

Key Parameters

Parameter	Value	Unit
BV_{DS}	40	V
$R_{DS(ON)}$ Max	2.6 @ $V_{GS} = 10\text{ V}$	$m\Omega$
	3.3 @ $V_{GS} = 4.5\text{ V}$	
$V_{GS(th)}$ typ	1.9	V
Q_g typ	70 @ $V_{GS} = 10\text{ V}$	nC

Absolute Maximum Ratings (at $T_a = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	40	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D	100	A
$T_c = 25^\circ\text{C}$		63	
$T_c = 100^\circ\text{C}$			
Peak Drain Current, Pulsed ¹⁾	I_{DM}	400	A
Single-Pulse Avalanche Current	I_{AS}	53	A
Single-Pulse Avalanche Energy ²⁾	E_{AS}	140	mJ
Power Dissipation	P_D	35.7	W
$T_c = 25^\circ\text{C}$			
Operating Junction and Storage Temperature Range	T_J, T_{stg}	- 55 to + 150	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Max.	Unit
Thermal Resistance from Junction to Case	$R_{\theta JC}$	3.5	$^\circ\text{C/W}$
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	50	$^\circ\text{C/W}$

¹⁾ Pulse Test: Pulse Width $\leq 100\text{ }\mu\text{s}$, Duty Cycle $\leq 2\%$, Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)} = 150^\circ\text{C}$.

²⁾ Limited by $T_{J(MAX)}$, starting $T_J = 25^\circ\text{C}$, $L = 0.1\text{ mH}$, $R_g = 25\text{ }\Omega$, $I_{AS} = 53\text{ A}$, $V_{GS} = 10\text{ V}$.

Characteristics at $T_a = 25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Min.	Typ.	Max.	Unit
STATIC PARAMETERS					
Drain-Source Breakdown Voltage at $I_D = 250\ \mu\text{A}$	BV_{DSS}	40	-	-	V
Drain-Source Leakage Current at $V_{DS} = 32\ \text{V}$	I_{DSS}	-	-	1	μA
Gate-Source Leakage Current at $V_{GS} = \pm 20\ \text{V}$	I_{GSS}	-	-	± 100	nA
Gate-Source Threshold Voltage at $V_{DS} = V_{GS}$, $I_D = 250\ \mu\text{A}$	$V_{GS(th)}$	1.5	-	2.5	V
Drain-Source On-State Resistance at $V_{GS} = 10\ \text{V}$, $I_D = 20\ \text{A}$ at $V_{GS} = 4.5\ \text{V}$, $I_D = 10\ \text{A}$	$R_{DS(on)}$	- -	2 -	2.6 3.3	$\text{m}\Omega$
DYNAMIC PARAMETERS					
Gate Resistance at $V_{DS} = 0\ \text{V}$, $f = 1\ \text{MHz}$	R_g	-	1.9	-	Ω
Input Capacitance at $V_{GS} = 0\ \text{V}$, $V_{DS} = 20\ \text{V}$, $f = 1\ \text{MHz}$	C_{iss}	-	4863	-	pF
Output Capacitance at $V_{GS} = 0\ \text{V}$, $V_{DS} = 20\ \text{V}$, $f = 1\ \text{MHz}$	C_{oss}	-	1985	-	pF
Reverse Transfer Capacitance at $V_{GS} = 0\ \text{V}$, $V_{DS} = 20\ \text{V}$, $f = 1\ \text{MHz}$	C_{rss}	-	70	-	pF
Total Gate Charge at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 10\ \text{V}$ at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 4.5\ \text{V}$	Q_g	- -	70 33	- -	nC
Gate Source Charge at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 10\ \text{V}$	Q_{gs}	-	18	-	nC
Gate Drain Charge at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 10\ \text{V}$	Q_{gd}	-	12	-	nC
Turn-On Delay Time at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 10\ \text{V}$, $R_g = 4.7\ \Omega$	$t_{d(on)}$	-	37	-	ns
Turn-On Rise Time at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 10\ \text{V}$, $R_g = 4.7\ \Omega$	t_r	-	61	-	ns
Turn-Off Delay Time at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 10\ \text{V}$, $R_g = 4.7\ \Omega$	$t_{d(off)}$	-	31	-	ns
Turn-Off Fall Time at $V_{DS} = 20\ \text{V}$, $I_D = 20\ \text{A}$, $V_{GS} = 10\ \text{V}$, $R_g = 4.7\ \Omega$	t_f	-	13	-	ns
Body-Diode PARAMETERS					
Drain-Source Diode Forward Voltage at $I_S = 20\ \text{A}$, $V_{GS} = 0\ \text{V}$	V_{SD}	-	-	1.3	V
Body-Diode Continuous Current	I_S	-	-	100	A
Body-Diode Continuous Current, Pulsed	I_{SM}	-	-	400	A
Body Diode Reverse Recovery Time at $I_S = 20\ \text{A}$, $di/dt = 100\ \text{A}/\mu\text{s}$	t_{rr}	-	45	-	ns
Body Diode Reverse Recovery Charge at $I_S = 20\ \text{A}$, $di/dt = 100\ \text{A}/\mu\text{s}$	Q_{rr}	-	46	-	nC

Electrical Characteristics Curves

Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 On-Resistance vs. Drain Current




Fig. 4 On-Resistance vs. Gate to Source Voltage




Fig. 5 On-Resistance vs. T_J





Fig. 6 Typical Body-Diode Forward Characteristics



Electrical Characteristics Curves

Fig. 7 Typical Junction Capacitance




Fig. 8 Drain-Source Leakage Current vs. T_j




Fig. 9 $V_{(BR)DSS}$ vs. Junction Temperature




Fig. 10 Gate Threshold Variation vs. T_j




Fig. 11 Gate Charge





Fig. 12 Safe Operation Area



Electrical Characteristics Curves

Fig.13 Normalized Maximum Transient Thermal Impedance($Z_{\theta JC}$)





Fig.14 Normalized Maximum Transient Thermal Impedance($Z_{\theta JA}$)



Test Circuits

Fig.1-1 Switching times test circuit




Fig.1-2 Switching Waveform




Fig.2-1 Gate charge test circuit




Fig.2-2 Gate charge waveform




Fig.3-1 Avalanche test circuit






Fig.3-2 Avalanche waveform



Package Outline Dimensions (Units: mm)

TO-220FB



UNIT	A	B	C	D	E	F	G	W	H	H1	K	L	L1	N
mm	2.9	6.8	0.7	15	1.5	0.9	2.54	10.2	4.7	2.5	3.1	16.8	9.4	1.4
	2.7	6.4	0.3	11	1.1	0.7	TYP	9.8	4.3	2.2	2.7	14.8	9.0	1.2

UNIT	P	P1	Q
mm	13.3	8.2	3.7
	12.7	7.6	3.5

Packing information

Package	Carton Quantity	Box Quantity	Base Quantity	Delivery Mode
TO-220FB	5 K / Carton	1 K / Box	50 pcs / Tube	Tube

Marking information

" TCT04N019L " = Part No.

" ***** " = Date Code Marking

Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice.