

RGV Series

Features

- 105°C, 2,000 hours assured
- Suitable for electronic equipment with high voltage circuits
- Flame retardant type capacitor
- RoHS Compliance




Sleeve & Marking Color: Black & White

Specifications

Items	Performance												
Category Temperature Range	-25°C ~ +105°C												
Capacitance Tolerance	±20% (at 120Hz, 20°C)												
Leakage Current (at 20°C)	$I = 3\sqrt{CV}$ or 1.5 mA whichever is smaller (after 5 minutes) Where, C = rated capacitance in μF , V = rated DC working voltage in V												
Tan δ (at 120 Hz, 20°C)	<table border="1"> <tr> <td>Rated Voltage</td> <td>400</td> <td>450</td> </tr> <tr> <td>Tanδ (max)</td> <td>0.25</td> <td>0.25</td> </tr> </table>	Rated Voltage	400	450	Tan δ (max)	0.25	0.25						
Rated Voltage	400	450											
Tan δ (max)	0.25	0.25											
Low Temperature Characteristics(at 120Hz)	<p>Impedance ratio shall not exceed the values given in the table below.</p> <table border="1"> <tr> <td>Rated Voltage</td> <td>400</td> <td>450</td> </tr> <tr> <td>Impedance Ratio</td> <td>Z(-25°C)/Z(+20°C)</td> <td>14 16</td> </tr> </table>	Rated Voltage	400	450	Impedance Ratio	Z(-25°C)/Z(+20°C)	14 16						
Rated Voltage	400	450											
Impedance Ratio	Z(-25°C)/Z(+20°C)	14 16											
Endurance	<table border="1"> <tr> <td>Test Time</td> <td>2,000 Hrs</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of initial value</td> </tr> <tr> <td>Tanδ</td> <td>Less than 200% of specified value</td> </tr> <tr> <td>Leakage Current</td> <td>Within specified value</td> </tr> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage with ripple current applied for 2,000 hours at 105°C.</p>	Test Time	2,000 Hrs	Capacitance Change	Within ±20% of initial value	Tan δ	Less than 200% of specified value	Leakage Current	Within specified value				
Test Time	2,000 Hrs												
Capacitance Change	Within ±20% of initial value												
Tan δ	Less than 200% of specified value												
Leakage Current	Within specified value												
Shelf Life Test	<table border="1"> <tr> <td>Test Time</td> <td>1,000 Hrs</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of initial value</td> </tr> <tr> <td>Tanδ</td> <td>Less than 150% of specified value</td> </tr> <tr> <td>Leakage Current</td> <td>Within specified value</td> </tr> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. The rated voltage shall be applied to the capacitors before the measurements (Refer to JIS C 5101-4 4.1).</p>	Test Time	1,000 Hrs	Capacitance Change	Within ±20% of initial value	Tan δ	Less than 150% of specified value	Leakage Current	Within specified value				
Test Time	1,000 Hrs												
Capacitance Change	Within ±20% of initial value												
Tan δ	Less than 150% of specified value												
Leakage Current	Within specified value												
Ripple Current and Frequency Multipliers	<table border="1"> <tr> <td>Frequency (Hz)</td> <td>60 (50)</td> <td>120</td> <td>500</td> <td>1k</td> <td>10k up</td> </tr> <tr> <td>Multiplier</td> <td>0.75</td> <td>1.0</td> <td>1.05</td> <td>1.10</td> <td>1.15</td> </tr> </table>	Frequency (Hz)	60 (50)	120	500	1k	10k up	Multiplier	0.75	1.0	1.05	1.10	1.15
Frequency (Hz)	60 (50)	120	500	1k	10k up								
Multiplier	0.75	1.0	1.05	1.10	1.15								

Diagram of Dimensions



Lead Spacing and Diameter

ϕD	16	18	20	22
P	7.5	7.5	10	10
ϕd	0.8		1.0	
α	2.0			
β	0.5			

Unit: mm

Dimension and Permissible Ripple Current

Dimension: $\phi D \times L$ (mm)
Ripple Current: mA/rms at 120 Hz, 105°C

μF	V. DC Contents	400V (2G)				450V (2W)			
		$\phi D \times L$	mA	* $\phi D \times L$	mA	$\phi D \times L$	mA	* $\phi D \times L$	mA
22	220	16×20	255			16×25	265		
33	330	16×25	350			16×35.5	365	16×31.5	360
47	470	16×35.5	420	16×31.5	400	18×31.5	425	16×35.5	420
56	560	16×35.5	440	18×25	450	16×35.5	445	16×31.5	435
68	680	16×35.5	500	18×31.5	510	20×35	530	18×35.5	510
82	820	18×35.5	525	20×30	530	22×30	545	18×40	525
100	101	18×40	585	20×35	595	22×35	592	20×40	595
120	121	20×40	625	22×35	632	22×45	656	22×40	632
150	151	22×40	654						

Note: Case size in mark of "*" is downsize

Part Numbering System

RGV Series	22 μF	±20%	450V	Bulk Package	Gas Type	16 ϕ ×25L	Pb-free and PET sleeve
RGV	220	M	2W	BK	-	1625	S
Series Name	Capacitance	Capacitance Tolerance	Rated Voltage	Lead Configuration & Package	Rubber Type	Case Size	Lead Wire and Sleeve type

Note: For more details, please refer to "Part Numbering System (Radial Type)"

All product specifications in the catalog are subject to change without notice. (CAT. 2017E1)

Radial