

## Features


- 105°C, 5,000 hours assured
- Suitable for switching power supplies, UPS, Ballast
- Smaller size with large permissible ripple current
- RoHS compliance



## Specifications

Items	Performance						
Category Temperature Range	160 ~ 400V			450V			
	-40°C ~ +105°C			-25°C ~ +105°C			
Capacitance Tolerance	±20% (at 120 Hz, 20°C)						
Leakage Current (at 20°C)	Time		after 5 minutes				
	Leakage Current		CV ≤ 1,000 I = 0.03CV(μA)	CV > 1,000 I = 0.02CV(μA)			
Where, C = rated capacitance in μF, V = rated DC working voltage in V							
Tanδ (at 120 Hz, 20°C)	Rated Voltage	160	200	250	350	400	450
	Tanδ (max)	0.20	0.20	0.20	0.24	0.24	0.24
Low Temperature Characteristics (at 120 Hz)	Impedance ratio shall not exceed the values given in the table below.						
	Rated Voltage	160	200	250	350	400	450
	Impedance Ratio	Z(-25°C) / Z(+20°C)	3	3	3	3	5
Endurance	Test Time		5,000 Hrs				
	Capacitance Change		Within ±20% of initial value				
	Tanδ		Less than 200% of specified value				
	Leakage Current		Within specified value				
	* The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied with rated ripple current for 5,000 hours at 105°C.						
Shelf Life Test	Test Time		1,000 Hrs				
	Capacitance Change		Within ±20% of initial value				
	Tanδ		Less than 200% of specified value				
	Leakage Current		Within specified value				
	* The above specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. The rated voltage shall be applied to the capacitors before the measurements (Refer to JIS C 5101-4 4.1).						
Ripple Current and Frequency Multipliers	Freq. (Hz)		120	1k	10k	100k up	
	Cap. (μF)	4.7 ~ 82	1.00	1.20	1.40	1.50	
		100 ≦	1.00	1.18	1.35	1.45	

## Diagram of Dimensions



Lead Spacing and Diameter Unit: mm

	10	12.5	16	18
φ D	10	12.5	16	18
P	5.0	5.0	7.5	7.5
φ d	0.6		0.8	
α	L < 20: 1.5, L ≥ 20: 2.0			
β	0.5			

### Dimension and Permissible Ripple Current

Dimension:  $\phi D \times L$ (mm)  
Ripple Current: mA/rms at 105°C

Rated Volt. (V <sub>DC</sub> ) Contents Cap.( $\mu$ F)	160V (2C)			200V (2D)			250V (2E)			350V (2V)			400V (2G)		
	$\phi D \times L$	Ripple Current		$\phi D \times L$	Ripple Current		$\phi D \times L$	Ripple Current		$\phi D \times L$	Ripple Current		$\phi D \times L$	Ripple Current	
		120 Hz	100k Hz		120 Hz	100k Hz		120 Hz	100k Hz		120 Hz	100k Hz		120 Hz	100k Hz
4.7													10×16	98	147
6.8										10×16	100	150	10×16	120	180
10							10×16	155	233	10×20	160	240	10×20	170	255
22	10×16	190	285	10×16	205	305	12.5×20	210	315	12.5×25	305	460	12.5×25	320	480
33	10×20	255	380	10×20	280	420	12.5×20	335	505	16×25	410	615	16×25	425	635
47	10×20	265	395	12.5×20	330	495	16×25	560	840	16×31.5	510	765	16×31.5	530	795
68	12.5×20	430	645	12.5×25	480	720	16×25	600	900	18×31.5	580	870	18×31.5	600	900
100	12.5×25	540	780	16×20	570	825	16×31.5	700	1,015	18×35.5	665	965	18×40	700	1,015
120	16×20	555	805	16×25	700	1,015	18×31.5	790	1,145	18×40	715	1,035	18×45	780	1,130
150	16×25	645	935	16×31.5	750	1,090	18×35.5	875	1,270						
180	16×31.5	745	1,080	18×31.5	830	1,205	18×40	980	1,420						
220	18×31.5	825	1,196	18×35.5	900	1,305	18×45	1,100	1,595						
270	18×35.5	930	1,350	18×40	1,100	1,595									
330	18×40	995	1,440	18×45	1,250	1,815									

Rated Volt. (V <sub>DC</sub> ) Contents Cap.( $\mu$ F)	450V (2W)		
	$\phi D \times L$	Ripple Current	
		120 Hz	100k Hz
4.7	10×16	105	158
6.8	10×20	170	255
10	12.5×20	280	420
22	16×25	405	610
33	16×31.5	490	735
47	18×31.5	575	865
68	18×40	665	1,000

### Part Numbering System

RXB Series    22 $\mu$ F     $\pm 20\%$     450V    Bulk Package    Gas Type    16  $\phi \times 25L$

**RXB**    **220**    **M**    **2W**    **BK**    -    **1625**    **XX**  
Series Name    Capacitance    Capacitance Tolerance    Rated Voltage    Lead Configuration and Package    Rubber Type    Case Size

**S** = Standard  
**KS** = AEC-Q200 Qualified, Safety Critical Application  
**LS** = AEC-Q200 Qualified, Non-Safety Critical Application