


Features

- Schottky barrier diodes
- Low forward voltage drop
- Solder dip 260 °C, 10 s
- Low profile, typical thickness 1.0mm
- Moisture sensitivity: level 1, per J-STD-020



eSGB (SMAF)

Typical Applications

For use in low voltage,high frequency inverters,free wheeling, and polarity protection application

Maximum Ratings (TA = 25 °C unless otherwise noted)

Parameter	Symbol	LS34A	LS345A	Unit
Maximum repetitive peak reverse voltage	VRRM	40	45	V
Maximum RMS voltage	VRMS	28	31.5	V
Maximum DC blocking voltage	VDC	40	45	V
Maximum average forward rectified current at TL (See Fig.1)	IF(AV)	3.0		A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	IFSM	55		A
Operating junction and storage temperature range	TJ, TSTG	- 55 to + 150		°C

Electrical Characteristics (TA = 25 °C unless otherwise noted)

Parameter	Test Conditions	Symbol	LS34A	LS345A	Unit
Maximum Instantaneous forward voltage	IF=3A, TA=25°C	VF	0.46		Volts
Maximum DC reverse current at rated DC blocking voltage	TA=25°C	IR	1		mA
Typical junction capacitance	4.0 V, 1 MHz	CJ	160		pF
Typical thermal resistance ¹⁾	junction to case	RθJC	50		°C/W
	junction to lead	RθJL	35		

Note1:Thermal resistance from junction to case and lead,mounted on PCB with 8.0×8.0mm copper pads

Ratings and Characteristics Curves

(TA = 25°C unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Reverse Characteristics




Figure 4. Typical Junction Capacitance






Figure 5. Typical Instantaneous Forward Characteristics

Package Outline Dimensions



DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.92	1.08	0.036	0.043
A1	0	0.1	0.000	0.004
B	1.25	1.45	0.049	0.057
C	0.1	0.25	0.004	0.010
D	2.6	2.8	0.102	0.110
E	4.1	4.3	0.161	0.169
L	0.7	1.1	0.028	0.043
HE	4.8	5.2	0.189	0.205

Soldering footprint



Packing Information

Packing quantities:

10,000 pcs/Reel, 12mm Tape, 13" Reel

Tape & Reel Specification

